

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : RT300G Viper Brite

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Refrigeration Technologies
1111 N. Armando St.
Anaheim, CA 92806 - USA
T 1-800-869-1407
www.refrigtech.com

1.4. Emergency telephone number

Emergency number : 1-800-255-3924 ChemTel; International Calls 1-813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1A H314

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage
Precautionary statements (GHS-US) : P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P264 - Wash ... thoroughly after handling
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P321 - Specific treatment (see ... on this label)
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable
Full text of H-phrases: see section 16

3.2. Mixture

RT300G Viper Brite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / SDS Created 01/01/2017

Name	Product identifier	%	GHS-US classification
sodium hydroxide	(CAS No)1310-73-2	5 - 40	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Aquatic Acute 3, H402

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes severe skin burns and eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Reactivity : Thermal decomposition generates : Corrosive vapours.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy/while nursing.
- Hygiene measures : Wash ... thoroughly after handling.

RT300G Viper Brite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / SDS Created 01/01/2017

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage temperature	: >= 25 (5 - 42) °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

sodium hydroxide (1310-73-2)		
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³

8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or face shield.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: Characteristic odour.
Odour threshold	: No data available
pH	: >= 8.5 (8 - 9)
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: <= 0 °C
Boiling point	: >= 100 °C
Flash point	: None
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: >= 1.17 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: No VOCs
-------------	-----------

RT300G Viper Brite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / SDS Created 01/01/2017

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapours.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

sodium hydroxide (1310-73-2)

LD50 dermal rabbit	1350 mg/kg (Rabbit; Literature,Rabbit; Literature)
Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: >= 8.5 (8 - 9)
Serious eye damage/irritation	: Not classified pH: >= 8.5 (8 - 9)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Readily biodegradable 28 days.

sodium hydroxide (1310-73-2)

LC50 fishes 1	45.4 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Solution >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h; Ceriodaphnia sp.; Nominal concentration)
LC50 fish 2	189 mg/l (48 h; Leuciscus idus)
TLM fish 1	99 mg/l (48 h; Lepomis macrochirus)
TLM fish 2	125 ppm (96 h; Gambusia affinis)

12.2. Persistence and degradability

RT300G Viper Brite

Persistence and degradability	Biodegradable in the soil. Biodegradable in water. Not established.
sodium hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.

RT300G Viper Brite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / SDS Created 01/01/2017

sodium hydroxide (1310-73-2)

Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

RT300G Viper Brite

Bioaccumulative potential	Not established.
---------------------------	------------------

sodium hydroxide (1310-73-2)

Bioaccumulative potential	Bioaccumulation: not applicable.
---------------------------	----------------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known. Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to ...
Ecology - waste materials	: Avoid release to the environment.

RT300G Viper Brite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / SDS Created 01/01/2017

SECTION 14: Transport information

In accordance with DOT

Transport document description	: UN1760 Corrosive liquids, n.o.s., 8, II
UN-No.(DOT)	: 1760
DOT NA no.	: UN1760
DOT Proper Shipping Name	: Corrosive liquids, n.o.s.
Department of Transportation (DOT) Hazard Classes	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Hazard labels (DOT)	: 8 - Corrosive



DOT Symbols	: G - Identifies PSN requiring a technical name
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

Additional information

Other information	: Less than 32 ounces ORMD, greater than 32 ounces UN1760.
-------------------	--

ADR

Transport document description	:
--------------------------------	---

Transport by sea

No additional information available

Air transport

No additional information available

RT300G Viper Brite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / SDS Created 01/01/2017

SECTION 15: Regulatory information

15.1. US Federal regulations

sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RQ (Reportable quantity, section 304 of EPA's List of Lists) : 1000 lb

15.2. International regulations

CANADA

RT300G Viper Brite

WHMIS Classification

Class E - Corrosive Material
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

sodium hydroxide (1310-73-2)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Aquatic Acute 3	Hazardous to the aquatic environment — AcuteHazard, Category 3
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H402	Harmful to aquatic life

NFPA health hazard

: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard


: 0 - Materials that will not burn.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.

NFPA specific hazard

: None



RT300G Viper Brite

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / SDS Created 01/01/2017

HMIS III Rating

Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 0 Minimal Hazard
Physical	: 1 Slight Hazard

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product