

# **MATERIAL SAFETY DATA SHEET**

**Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200**

Date of Prep: 11/30/10

## SECTION 1

SUNNYSIDE CORPORATION  
225 CARPENTER AVENUE  
WHEELING, ILLINOIS 60090  
EMERGENCY TELEPHONE

(847) 541-5700  
(800) 424-9300

FOR INFORMATION:

(847) 541-5700

- SUNNYSIDE CORPORATION  
- CHEM TREC

Product Class: Mixed Solvents  
Trade Name: VOC Compliant General Purpose Thinner

Manufacturer's Code:  
NPCA HMIS:

476  
Health: 1  
Flammability: 3  
Reactivity: 0

Product Appearance and Odor: Clear, water-white liquid; typical, pungent odor.

## SECTION 2 -- HAZARDOUS INGREDIENTS

### OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Acetone	67-64-1		500 PPM	750 PPM	750 PPM	1000 PPM	213 MM Hg @ 75° F
Light Aliphatic Solvent Naphtha	64742-89-8		300 PPM		300 PPM	400 PPM	45 MM Hg @ 25° C

## SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

INHALATION:	Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. If breathing is difficult, qualified medical personnel may administer oxygen and continue to monitor. Keep at rest. Get medical attention immediately.
EYE CONTACT:	Flush eyes immediately with water for at least 15 minutes. Get prompt medical attention.
SKIN CONTACT:	Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse. Get medical attention if skin irritation develops or persists.
INGESTION:	If swallowed, do not induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

## SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	133° (F) (I.B.P.)	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	100%
Weight Per Gallon:	6.61 Lbs.	VOC: 23 g/l.	
Solubility in Water:	Complete		

**SECTION 5 -- FIRE AND EXPLOSION DATA**

Flammability Classification:	Flammable Liquid - Class IB.
Flash Point:	0° (F) (Tag, Closed Cup).
Autoignition Temperature:	Not Available
Lower Explosive Limit:	Not Available
Extinguishing Media:	Either allow fire to burn under controlled conditions or extinguish with alcohol resistant foam and dry chemical. Try to cover liquid spills with foam.
Unusual Fire and Explosion Hazards:	Extremely flammable. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.
Special Fire Fighting Procedures:	Use water spray to cool fire exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

**SECTION 6 -- HEALTH HAZARD DATA**

THRESHOLD LIMIT VALUE: EFFECTS OF OVEREXPOSURE	See Section 2.
Inhalation:	Vapors or mist may cause irritation of the nose and throat. Inhalation may cause dizziness, drowsiness, loss of coordination, disorientation, headache, nausea, and vomiting. In poorly ventilated areas or confined spaces, unconsciousness and asphyxiation may result.
Skin Contact:	Prolonged or repeated skin contact may cause irritation, discomfort and dermatitis.
Eye Contact:	Severely irritating and may injure cornea if not removed promptly. High vapor concentrations are also irritating.
Ingestion:	Product may be harmful or fatal if swallowed. Material is a pulmonary aspiration hazard. Material can enter lungs and cause damage. Ingestion of this product may cause central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death.
Carcinogenicity:	The components of this product has not been identified as a carcinogen by NTP, IARC, or OSHA.

**SECTION 7 -- REACTIVITY DATA**

Stability:	Stable
Conditions to Avoid:	Heat, sparks and flame.
Incompatibility (Materials to Avoid):	Caustics, amines, alkanolamines, aldehydes, ammonia, strong oxidizing agents, and chlorinated compounds.
Hazardous Decomposition Products:	Thermal decomposition may yield carbon monoxide, carbon dioxide, aldehydes and ketones.
Hazardous Polymerization:	Will not occur.

**SECTION 8 -- SPILL OR LEAK PROCEDURES**

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapors or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

**SECTION 9 -- SAFE HANDLING AND USE INFORMATION**

Respiratory Protection:	Where concentrations in air may exceed occupational exposure limits, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.
Ventilation:	Exposure levels should be maintained below applicable exposure limits - see Section 2. This product should not be used in confined spaces, or in a manner that will allow accumulation of high vapor concentrations. However, for controlled industrial uses when this product is used in confined spaces, heated above ambient temperatures or agitated, the use of explosion proof ventilation equipment is necessary.
Protective Gloves:	Chemical resistant gloves (Neoprene or Natural Rubber).
Eye Protection:	Chemical safety goggles and a face shield. Emergency eyewash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Other Protective Equipment:	Impervious clothing or boots where needed, eyewash facility and a safety shower.

**SECTION 10 -- SPECIAL PRECAUTIONS**

Dept. of Labor Storage Category: Flammable Liquid-Class IB.

Hygienic Practices: Keep away from heat, sparks and flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.

Additional Precautions: Ground containers when transferring liquid to prevent static accumulation and discharge. Additional information regarding safe handling of products with static accumulation potential can be ordered by contacting the American Petroleum Institute (API) for API Recommended Practice 2003, entitled "Protection Against Ignitions Arising Out of Static, Lighting, and Stray Currents" (American Petroleum Institute, 1720 L Street Northwest, Washington, DC 20005), or the National Fire Protection Association (NFPA) for NFPA 77 entitled "Static Electricity" (National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101).

Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

**SECTION 11 -- ADDITIONAL INFORMATION**

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
NONE	NONE	NONE

SARA Title III Hazard Categories: Immediate (Acute) Health, Delayed (Chronic) Health, Fire

Common Names: Lacquer Reducer, solvent mixture.

California Proposition 65: This product contains trace amounts of Benzene and Toluene which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65.

TRANSPORTATION (U.S. D.O.T. land transportation in packages of 119 gallons or less)

U.S. D.O.T. Proper Shipping Name: Paint Related Materials

U.S. D.O.T. Hazard Class: 3

U.S. D.O.T. Packing Group: II

U.S. D.O.T. I.D. Number: UN 1263

U.S. D.O.T. Hazardous Substance: Acetone RQ 5000 lbs.

Refer to 49 CFR for additional information. Exceptions or exemptions may exist for smaller quantities.