# SAFETY DATA SHEET



1. Identification

Product identifier BEHR® PREMIUM PLUS Interior/Exterior Hi-Gloss Enamel - Ultra Pure White

Other means of identification

Product number 8050

Recommended use Architectural Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**Supplier** Behr Process Corp.

1801 E. St. Andrew Place Santa Ana. CA 92705

**Telephone** 714-545-7101 **Emergency telephone** +1 760 476 3962

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1A

Specific target organ toxicity, repeated Category 2 (kidney)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. May cause damage to organs (kidney) through prolonged or

repeated exposure.

**Precautionary statement** 

**Prevention** Do not breathe mist/vapors. Contaminated work clothing must not be allowed out of the

workplace. Wear protective gloves.

**Response** If on skin: Wash with plenty of water. Get medical advice/attention if you feel unwell. If skin

irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

## 3. Composition/information on ingredients

## Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	10 - 30
Ethylene glycol	107-21-1	1 - 5
Silicon dioxide, crystalline silica-free	7631-86-9	1 - 5

BEHR® PREMIUM PLUS Interior/Exterior Hi-Gloss Enamel - Ultra Pure White

951440 Version #: 02 Revision date: 20-May-2020 Issue date: 16-January-2020

1,2-Benzisothiazol-3(2H)-one	2634-33-5	0 - 0.1
5-Chloro-2-methyl-2H-isothiazo	26172-55-4	0 - 0.1

**Composition comments** 

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact**Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Dines with water. Cet medical attention if irritation devalors and persists

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important May symptoms/effects, acute and chro

symptoms/effects, acute and delayed

May cause an allergic skin reaction. Dermatitis. Rash. Edema. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. **Environmental precautions**Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

### Occupational exposure limits

HE OSHA Table	7 1 Limits for	· Air Contaminante	(29 CFR 1910.1000)
US. USHA Table	Z-1 LIMITS TO	r Air Contaminants	(29 CFR 1910.1000)

Components	Type	Value	Form
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.1000)			
Components	Туре	Value	Form
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	0.8 mg/m3	
		20 mppcf	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Chemical F	lazards		
Components	Туре	Value	
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)	TWA	6 mg/m3	

**Biological limit values** 

Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Skin protection

Other Use of an impervious apron is recommended.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

BEHR® PREMIUM PLUS Interior/Exterior Hi-Gloss Enamel - Ultra Pure White 951440 Version #: 02 Revision date: 20-May-2020 Issue date: 16-January-2020

**Form** Liquid. White. Color Odor Slight.

**Odor threshold** Not available.

7 - 10 pН

Melting point/freezing point Not available. > 99 °F (> 37.2 °C) Initial boiling point and boiling

range

Flash point Not applicable. **Evaporation rate** Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Vapor pressure Not available. Not available. Vapor density

1.26 Relative density

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient

Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity** 50 - 140 ku (25 °C)

Other information

**Density** 10.49 lbs/gal **Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

VOC 57 g/l (including water)(Material)

147 g/l (excluding water)(Coating)

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

No hazardous decomposition products are known.

products

# 11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash. Edema. Prolonged exposure may cause

chronic effects.

Information on toxicological effects

**Acute toxicity** 

Components **Species Test Results** 

Ethylene glycol (CAS 107-21-1)

**Acute Dermal** 

LD50 Rabbit 9530 mg/kg

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Acute **Dermal** 

LD50 Rabbit > 5000 mg/kg, 24 Hours

Inhalation

Dust

LC50 Rat > 0.14 mg/l, 4 Hours

Oral

LD50 Rat > 3300 mg/kg

Titanium dioxide (CAS 13463-67-7)

Respiratory or skin sensitization

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eve damage/eve Direct contact with eyes may cause temporary irritation.

irritation

Not a respiratory sensitizer. Respiratory sensitization

May cause an allergic skin reaction. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the Carcinogenicity

product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon dioxide, crystalline silica-free (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

**NTP Report on Carcinogens** 

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure.

Not an aspiration hazard. **Aspiration hazard** 

Prolonged inhalation may be harmful. **Chronic effects** 

12. Ecological information

Harmful to aquatic life with long lasting effects. **Ecotoxicity** 

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

### 15. Regulatory information

**US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Ethylene glycol (CAS 107-21-1)

Listed.

SARA 304 Emergency release notification

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**Toxic Substances Control Act (TSCA)** 

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Respiratory or skin sensitization

categories

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

**Chemical name** CAS number % by wt. 107-21-1 1 - 5 Ethylene glycol

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

SDS US 6/7

(SDWA)

951440 Version #: 02 Revision date: 20-May-2020 Issue date: 16-January-2020

## **US state regulations**

#### **US. Massachusetts RTK - Substance List**

Ethylene glycol (CAS 107-21-1)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

## US. New Jersey Worker and Community Right-to-Know Act

Ethylene glycol (CAS 107-21-1)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

Ethylene glycol (CAS 107-21-1)

Silicon dioxide, crystalline silica-free (CAS 7631-86-9)

Titanium dioxide (CAS 13463-67-7)

#### **US. Rhode Island RTK**

Ethylene glycol (CAS 107-21-1) Titanium dioxide (CAS 13463-67-7)

## 16. Other information, including date of preparation or last revision

Issue date 16-January-2020 Revision date 20-May-2020

Version # 02

**Further information** HMIS® is a registered trade and service mark of the ACA.

G - Safety Glasses, Gloves, Vapor Respirator

HMIS® ratings Health: 2\*

Flammability: 0 Physical hazard: 0 Personal protection: G

**List of abbreviations** PEL: Permissible Exposure Limit.

TWA: Time Weighted Average Value. STEL: Short-Term Exposure Limit.

Ceiling: Short Term Exposure Limit Ceiling value.

LD50: Lethal Dose 50%.

LC50: Lethal Concentration 50%.

DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IMDG Code: International Maritime Dangerous Goods Code.

MARPOL: International Convention for the Prevention of Pollution from Ships.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

References HSDB® - Hazardous Substances Data Bank

**Disclaimer**Behr Process Corp cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

951440 Version #: 02 Revision date: 20-May-2020 Issue date: 16-January-2020 7 / 7