

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 03/19/2020

Version 1.8

SECTION 1. Identification**Product identifier**

Product number	EX0276
Product name	Ethyl Alcohol 200 Proof GR ACS
Synonyms	EtOH
CAS-No.	64-17-5

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Reagent for analysis
-----------------	----------------------

Details of the supplier of the safety data sheet

Company	EMD Millipore Corporation 400 Summit Drive Burlington Massachusetts 01803 United States of America General Inquiries: +1 800-645-5476 Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5) MilliporeSigma is a business of Merck KGaA, Darmstadt, Germany.
---------	--

Emergency telephone	800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week
----------------------------	--

SECTION 2. Hazards identification**GHS Classification**

Flammable liquid, Category 2, H225
Eye irritation, Category 2A, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms



SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

Signal Word

Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. Composition/information on ingredients

Formula	C ₂ H ₅ OH	C ₂ H ₆ O (Hill)
Synonyms	EtOH	
Molar mass	46.07 g/mol	

Hazardous ingredients

Chemical name (Concentration)

CAS-No.

ethanol (>= 90 % - <= 100 %)

64-17-5

Exact percentages are being withheld as a trade secret.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

SECTION 4. First aid measures

Description of first-aid measures

Inhalation

After inhalation: fresh air.

Skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

Ingestion

After swallowing: immediately make victim drink water (two glasses at most).
Consult a physician.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria,
Nausea, Vomiting

Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Dry powder, Water

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback.

Forms explosive mixtures with air at ambient temperatures.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapors possible in the event of fire.

Advice for firefighters

Special protective equipment for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. Handling and storage

Precautions for safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Store at room temperature.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

SECTION 8. Exposure controls/personal protection

Exposure limit(s)

Components

Basis	Value	Threshold limits	Remarks
<i>ethanol 64-17-5</i>			
ACGIH	Short Term Exposure Limit (STEL):	1,000 ppm	
NIOSH/GUIDE	Recommended exposure limit (REL):	1,000 ppm 1,900 mg/m ³	
OSHA_TRANS	PEL:	1,000 ppm 1,900 mg/m ³	
Z1A	Time Weighted Average (TWA):	1,000 ppm 1,900 mg/m ³	

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

Eye/face protection

Safety glasses

Safety glasses

Hand protection

full contact:

Glove material: butyl-rubber
Glove thickness: 0.7 mm
Break through time: 480 min

splash contact:

Glove material: Nitrile rubber
Glove thickness: 0.40 mm
Break through time: 120 min

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 898 Butoject® (full contact), KCL 730 Camatril® -Velours (splash contact).
The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.
This recommendation applies only to the product stated in the safety data sheet and supplied by us as well as to the purpose specified by us. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment:

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapors/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapors of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are performed according to the instructions of the producer.

These measures have to be properly documented.

SECTION 9. Physical and chemical properties

Physical state	liquid
Color	colorless
Odor	alcohol-like
Odor Threshold	0.1 - 5058.5 ppm
pH	7.0 at 10 g/l 68 °F (20 °C)
Melting point	-174.1 °F (-114.5 °C)
Boiling point/boiling range	172.9 °F (78.3 °C) at 1,013 hPa
Flash point	55 °F (13 °C) Method: c.c.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number	EX0276	Version 1.8
Product name	Ethyl Alcohol 200 Proof GR ACS	

Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	3.1 %(V)
Upper explosion limit	27.7 %(V)
Vapor pressure	59 hPa at 68 °F (20 °C)
Relative vapor density	1.6
Density	0.790 - 0.793 g/cm ³ at 68 °F (20 °C)
Relative density	No information available.
Water solubility	at 68 °F (20 °C) completely miscible
Partition coefficient: n-octanol/water	log Pow: -0.31 (experimental) (Lit.) Bioaccumulation is not expected.
Autoignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	1.2 mPa.s at 68 °F (20 °C)
Explosive properties	Not classified as explosive.
Oxidizing properties	none
Ignition temperature	797 °F (425 °C) Method: DIN 51794
Conductivity	< 1 µS/cm

SECTION 10. Stability and reactivity

Reactivity

Page 7 of 15

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

Vapors may form explosive mixture with air.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide, perchlorates, perchloric acid, Nitric acid, mercury(II) nitrate, permanganic acid, Nitriles, peroxy compounds, Strong oxidizing agents, nitrosyl compounds, Peroxides, sodium, Potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metallic oxides, uranium hexafluoride, iodides, Chlorine, Alkali metals, Alkaline earth metals, alkali oxides, Ethylene oxide

silver, with, Nitric acid

silver compounds, with, Ammonia

potassium permanganate, with, conc. sulfuric acid

Risk of ignition or formation of inflammable gases or vapors with:

halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, Fluorine, hydrides, Oxides of phosphorus, platinum

Nitric acid, with, potassium permanganate

Conditions to avoid

Warming.

Incompatible materials

rubber, various plastics

Hazardous decomposition products

no information available

SECTION 11. Toxicological information

Information on toxicological effects

Likely route of exposure

Inhalation, Eye contact, Skin contact

Target Organs

Eyes

Skin

Respiratory system

Central nervous system

Liver

Blood

reproductive system

Page 8 of 15

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

Acute oral toxicity

LD50 Rat: 10,470 mg/kg
OECD Test Guideline 401

Symptoms: Nausea, Vomiting

Acute inhalation toxicity

LC50 Rat: 124.7 mg/l; 4 h ; vapor
OECD Test Guideline 403

Symptoms: slight mucosal irritations

Skin irritation

Rabbit

Result: No skin irritation
OECD Test Guideline 404

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation

Rabbit

Result: Eye irritation
OECD Test Guideline 405

Causes serious eye irritation.

Sensitization

Local lymph node assay (LLNA) Mouse
Result: negative
Method: OECD Test Guideline 429

Genotoxicity in vitro

Ames test

Salmonella typhimurium

Result: negative
Method: OECD Test Guideline 471

In vitro mammalian cell gene mutation test

MOUSE LYMPHOMA TEST

Result: negative
Method: OECD Test Guideline 476

Carcinogenicity

Carcinogen classifications of IARC, NTP, California proposition 65 for Ethanol CAS 64-17-5 apply to beverage use only. This product is NOT intended for this use.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

Reproductive toxicity

Application Route: Oral

Mouse

Method: OECD Test Guideline 416

Specific target organ systemic toxicity - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
ACGIH	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Further information

Systemic effects:

euphoria

After absorption:

Dizziness, inebriation, narcosis, respiratory paralysis

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

Toxicity to fish

flow-through test EC50 Pimephales promelas (fathead minnow): 15,300 mg/l; 96 h

Analytical monitoring: yes

US-EPA

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 9,268 - 14,221 mg/l; 48 h (IUCLID)

Toxicity to algae

IC5 Scenedesmus quadricauda (Green algae): 5,000 mg/l; 7 d (Lit.)

Toxicity to bacteria

EC5 Pseudomonas putida: 6,500 mg/l; 16 h (IUCLID)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

semi-static test NOEC Daphnia magna (Water flea): 9.6 mg/l; 9 d
(ECHA)

Persistence and degradability

Biodegradability

94 %

OECD Test Guideline 301E

Readily biodegradable.

Biochemical Oxygen Demand (BOD)

930 - 1,670 mg/g (5 d)

(Lit.)

Theoretical oxygen demand (ThOD)

2,100 mg/g

(Lit.)

Ratio COD/ThBOD

90 %

(Lit.)

Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: -0.31

(experimental)

(Lit.) Bioaccumulation is not expected.

Mobility in soil

No information available.

Additional ecological information

No interference with wastewater treatment plants are to be expected when used properly.

Discharge into the environment must be avoided.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14. Transport information

Land transport (DOT)

UN number UN 1170
Proper shipping name ETHANOL
Class 3
Packing group II
Environmentally hazardous --

Air transport (IATA)

UN number UN 1170
Proper shipping name ETHANOL
Class 3
Packing group II
Environmentally hazardous --
Special precautions for user no

Sea transport (IMDG)

UN number UN 1170
Proper shipping name ETHANOL
Class 3
Packing group II
Environmentally hazardous --
Special precautions for user yes
EmS F-E S-D

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number EX0276
Product name Ethyl Alcohol 200 Proof GR ACS

Version 1.8

SECTION 15. Regulatory information

United States of America

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 302

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

DEA List I

Not listed

DEA List II

Not listed

US State Regulations

Massachusetts Right To Know

Components

ethanol

Pennsylvania Right To Know

Components

ethanol

New Jersey Right To Know

Components

ethanol

California Prop 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number

EX0276

Version 1.8

Product name

Ethyl Alcohol 200 Proof GR ACS

SECTION 16. Other information

Training advice

Provide adequate information, instruction and training for operators.

Labeling

Hazard pictograms



Signal Word

Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

Precautionary Statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Full text of H-Statements referred to under sections 2 and 3.

H225

Highly flammable liquid and vapor.

H319

Causes serious eye irritation.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date 03/19/2020

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

SAFETY DATA SHEET

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number	EX0276
Product name	Ethyl Alcohol 200 Proof GR ACS

Version 1.8

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.