

Search

GO

MSDS : FE-501 GLOSS BLACK FRESH & EASY SPRAY ENAMEL

CAS : 74-98-6
106-97-8
100-41-4
1330-20-7
67-64-1

NAME : propane
butane
ethylbenzene
xylene
acetone

Start Download (Fi

File size: 487KB. Full Ver

Convert All PDF Files (Free)

pdfhubonline.com

OPEN

DUTCH BOY PAINTS -- FE-501 GLOSS BLACK FRESH & EASY SPRAY ENAMEL

Material Safety Data Sheet

MSDS Num: CLBTR

MSDS NAME: FE-501 GLOSS BLACK FRESH & EASY SPRAY ENAMEL

Responsible Party

Name: DUTCH BOY PAINTS

Box: 6709

City: CLEVELAND OH 44101

Info Phone: (216) 566-2902

Emergency Phone Number: 216-566-2917

Review Ind: Y

Published: Y

Contractor Summary

Name: DUTCH BOY PAINTS

Box: 6709

City: CLEVELAND OH 44101

Phone: (216) 566-2902

Ingredients

Cas: 74-98-6

RTECS #: TX2275000

Name: PROPANE

Percent by Wt: 14.

OSHA PEL: 1000 PPM

Cas: 106-97-8

RTECS #: EJ4200000

Name: BUTANE

Percent by Wt: 13.

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM

ACGIH STEL: NOT ESTABLISHED

Cas: 100-41-4
RTECS #: DA0700000
Name: ETHYLBENZENE
Percent by Wt: 3.
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
ACGIH STEL: 543 MG/M3;125 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE
Percent by Wt: 15.
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE
Percent by Wt: 47.
OSHA PEL: 750 PPM
ACGIH TLV: 750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS
=====

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Signs And Symptoms Of Overexposure: IRRITATION OF EYES, SKIN AND RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH. HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE.

Medical Cond Aggravated By Exposure: NONE GENERALLY RECOGNIZED.

First Aid: INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE. EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE SEVERAL GLASSES OF WATER AND SEEK MEDICAL ATTENTION.

Handling and Disposal

=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Waste Disposal Methods: WASTE FROM THESE PRODUCTS MAY BE HAZARDOUS AS DEFINED UNDER THE RESOURCE CONSERVATION AND RECOVERY ACT 40 CFR 261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE NUMBERS. DO NOT INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Handling And Storage Precautions: CONTENTS ARE EXTREMELY FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE EXPLOSIVELY. DURING USE AND UNTIL ALL VAPORS ARE GONE: KEEP AREA VENTILATED-DO NOT SMOKE-EXTINGUISH ALL FLAMES, PILOT LIGHTS, AND HEATERS-TURN OFF STOVES, ELECTRIC TOOLS.

Other Precautions: CONSULT NFPA CODE. USE APPROVED BONDING AND GROUNDING

PROCEDURES. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPERATURE ABOVE 120 F. HEAT FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: PMCC

Flash Point: <-17.6C, 0.F

Lower Limits: 0.7

Upper Limits: 12.8

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures: FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
Control Measures
=====

Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS IN SECTION II. WHEN SANDING OR ABRADING THE DRIED FILM, WEAR A DUST/MIST RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST NON-VOLATILE MATERIALS IN SECTION II

Ventilation: LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IN SECTION II IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves: WEAR GLOVES WHICH ARE RECOMMENDED BY GLOVE SUPPLIER FOR PROTECTION

Eye Protection: WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS.

Work Hygienic Practices: WASH HANDS AFTER USING.

Supplemental Safety and Health: NFPA CODE 30B: LEVEL 3 AEROSOLS RED LABEL: EXTREMELY FLAMMABLE, FLASH BELOW 21 F USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. RATING: HEALTH=2; FLAMMABILITY=4; REACTIVITY=0

=====
Physical/Chemical Properties
=====

B.P. Text: <0-600F

Vapor Density: >AIR

Volatile Org Content %: 45

Evaporation Rate & Reference: FASTER THAN ETHER

Percent Volatiles by Volume: >75

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: NONE KNOWN.

Materials To Avoid: NONE KNOWN.

Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF METALS IN SECTION II.

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

Toxicological Information: PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS IN SECTION II MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY, BLOOD-FORMING, CARDIOVASCULAR, AND REPRODUCTIVE SYSTEMS. RATS EXPOSED TO TITANIUM DIOXIDE DUST AT 250 MG/M3 DEVELOPED LUNG CANCER, HOWEVER, SUCH EXPOSURE LEVELS ARE NOT ATTAINABLE IN THE WORKPLACE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

=====
Ecological Information
=====

=====

MSDS Transport Information

=====

Regulatory Information

=====

Sara Title III Information: ETHYLBENZENE, XYLENE

Federal Regulatory Information: TSCA CERTIFICATION: ALL CHEMICALS IN THIS PRODUCT ARE LISTED, OR ARE EXEMPT FROM LISTING, ON THE TSCA INVENTORY.

State Regulatory Information: CALIFORNIA PROPOSITION 65: THESE PRODUCTS CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

=====

Other Information

=====

Other Information: THE ABOVE INFORMATION PERTAINS TO THESE PRODUCTS AS CURRENTLY FORMULATED, AND IS BASED ON THE INFORMATION AVAILABLE AT THIS TIME. ADDITION OF REDUCERS OR OTHER ADDITIVES TO THESE PRODUCTS MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCTS. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.

=====

HAZCOM Label

=====

MSDS NAME: FE-501 GLOSS BLACK FRESH & EASY SPRAY ENAMEL

Assigned IND: Y

Company: DUTCH BOY PAINTS

PO Box: 6709

City: CLEVELAND OH

Zipcode: 44101

Health Emergency Phone: 216-566-2917

Label Required IND: Y

Date Of Label Review: 04/16/2001

Status Code: A

Origination Code: G

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.

*** END OF RECORD ***

PDF Hub Online



Download PDF (Free)

[Search More](#)

[GO](#)

NAME	CAS
<u>PVC GRAY CEMENT, UNI-WELD SERIES 1600, 1700, 1800, 1900</u>	109-99-9 78-93-3 108-94-1 9002-86-2 112945-52-5 67-64-1
<u>PVC GRAY CEMENT,CHEM-TECH:5500;5600</u>	109-99-9 78-93-3 108-94-1 9002-86-2 112945-52-5 67-64-1
<u>SAFTEY MATCH</u>	
<u>FLASHBREAKER 1</u>	
<u>REGENT RUBBER STAMP INK RED</u>	
<u>CODING & MARKING INK 4134, BLACK,WHITE,BLUE,GRAY,BRONZE</u>	
<u>CODING & MARKING INK 4134, BLACK,WHITE,BLUE,GRAY,BRONZE</u>	
<u>SO SURE STENCIL INK RED</u>	67-64-1 74-98-6 108-88-3 8032-32-4 106-97-8 75-28-5 1330-20-7 100-41-4
<u>SO SURE STENCIL INK WHITE</u>	67-64-1 74-98-6 108-88-3 8032-32-4 106-97-8 75-28-5 1330-20-7
<u>SO SURE STENCIL INK YELLOW</u>	67-64-1 74-98-6 108-88-3 106-97-8 75-28-5 1330-20-7 123-86-4 8006-39-1
<u>CORRECTION FLUID</u>	71-55-6 61788-76-9
<u>PIGMENT ONE INKED RIBBONS FOR MATRIX</u>	
<u>4134 CODING AND MARKING INK YELLOW</u>	
<u>PVC GREY CEMENT,PLASTI-WELD SERIES:203,403</u>	109-99-9 78-93-3 108-94-1 9002-86-2 112945-52-5 67-64-1
<u>2023STRATA BLUE INK MARKING</u>	
<u>X STAMPER INK XLR-20 WHITE</u>	
<u>X STAMPER INK XLR-20 WHITE</u>	
<u>FRAME FAST 280 ADHESIVE</u>	7085-85-0
<u>FRAME FAST AEROSOL ACTIVATOR 304</u>	67-64-1 106-97-8 74-98-6
<u>FIREPOWER FP-10 LUBRICANT ELITE</u>	

<u>BABY POWDER</u>	
<u>MIL-PRF-87257A, MLS 97-057</u>	128-37-0 29385-43-1 1330-20-7
<u>FINGERTIP MOISTENER</u>	
<u>IBM, BLACK NYLON RIBBON</u>	32131-17-2 8005-02-5 1325-86-6 548-62-9 6358-85-6 112-80-1 1333-86-4
<u>SO-SURE WHITE 37875 (54-370) P ENAMEL</u>	74-98-6 106-97-8 108-88-3 67-64-1 64475-85-0 75-28-5
<u>SO-SURE CORROSION PREVENTION COMPOUND</u>	67-63-0 811-97-2 8032-32-4 8030-30-6 78-83-1 107-98-2 108-88-3 71-36-3 64741-65-7 64741-97-5 25619-56-1
<u>PITT PENN PREMIUM HEAVY DUTY MILITARY (SEE SUPPL DAT A).</u>	
<u>V.O.C. COMPLIANT SPRAY PAINT (AEROSOL).</u>	1330-20-7 74-98-6 115-10-6 110-12-3 107-87-9 108-10-1 95-63-6 71-36-3 64742-95-6
<u>FORMULA 2500 OVEN CLEANER 6221-6</u>	
<u>SCOTCH-WELD (TM) DP-100 NS (PART A) TRANSLUCENT EPOXY ADHESI</u>	
<u>SCOTH-WELD (TM) DP-100 NS (PART B) TRANSLUCENT EPOXY ADHESIV</u>	
<u>AC-236 CLASS B BASE</u>	
<u>AC-236 ACCELERATOR</u>	
<u>PITT PENN PREMIUM HEAVY DUTY MILITARY ANTIFREEZE, PR</u>	
<u>EMIXED</u>	
<u>PITT PENN PREMIUM HEAVY DUTY MILITARY ANTIFREEZE, PR</u>	
<u>EMIXED</u>	
<u>PITT PENN PREMIUM HEAVY DUTY MILITARY ANTIFREEZE</u>	
<u>DINITROL AV 30</u>	
<u>CARBON DIOXIDE GAS</u>	
<u>DEMAND CS</u>	
<u>81878 101BR ULTRA COPPER HIGH TEMP RTV SILICONE GAS</u>	70131-67-8
<u>KET MAK</u>	63148-62-9 68611-44-9 2224-33-1 12001-26-2 23843-64-3

[POLYURETHANE AEROSOL COLORS](#)

96-29-7
1309-37-1
123-86-4
1330-20-7
8052-41-3
67-64-1
74-98-6
75-28-5
106-97-8

[GARD ANTI RUST SAE 30](#)

[5506331 MOLYDAG 254](#)

[DP40 NON SANDING EPOXY PRIMER](#)

107-98-2
108-88-3
110-19-0
11103-86-9
1330-20-7
1333-86-4
13463-67-7
14807-96-6
25068-38-6
25086-48-0
67-63-0
7727-43-7
7789-06-2
78-93-3
90438-79-2

[ACMI #4134 CODING & MARKING INK](#)

[STAR SOLV](#)

[PRO-SEAL 870 A-2 BASE 0870A65](#)

28470-78-2
13463-67-7
1317-65-3
108-88-3
68611-50-7

[HEL-CAT #5D625302](#)

[FE-501 GLOSS BLACK FRESH & EASY SPRAY ENAMEL](#)

74-98-6
106-97-8
100-41-4
1330-20-7
67-64-1

[CRYSTAL SIMPLE GREEN](#)

111-76-2