

Date Prepared: 04-Nov-2013

Revised: 1-Aug-2018

SDS ID: GLS_GHS_001



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product trade name(s): KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Common Name(s): Kaolinitic Clay, Ball Clay

Chemical Formula: $\text{Al}_2\text{Si}_2\text{O}_5(\text{OH})_4$

CAS Number: 999999-99-4

Physical Form: Light gray to brown solid

Recommended Uses: Non-exhaustive list: Ceramics, ceramic glazes, porcelain insulators, gypsum wallboard, ceiling tile, coal tar sealing emulsions

Restrictions on Use: Food ingredient, cosmetic ingredient, agricultural feed, pesticide

Manufacturer's Name: Kentucky-Tennessee Clay Company

Address: 100 Mansell Court East
Suite 300
Roswell, GA 30076

Telephone: 770-594-0660

Fax: 770-645-3460

Customer Service: 800-814-4538

Emergency Telephone: **For Chemical Emergency Call CHEMTREC (24 hours): 1-800-424-9300**
(US, Canada, Puerto Rico, Virgin Islands)
1-703-527-3887 (Outside Above Area) collect calls accepted

SECTION 2: HAZARDS IDENTIFICATION

Classification:

| | |
|--|--------------------------|
| Contains Crystalline Silica | |
| Eye Damage/Irritation | Category 2 |
| Skin Corrosion/Irritation | Category 2 |
| Specific Target Organ Toxicity – Single Exposure | Category 3 – Respiratory |
| Specific Target Organ Toxicity – Repeated Exposure | Category 1 – Respiratory |

Label Elements:



Signal Word:

DANGER

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Hazard Statements:**H372:** Causes damage to lung through prolonged or repeated inhalation.**Precautionary Statements:****P260:** Do not breathe dust.**P285:** In case of inadequate ventilation wear respiratory protection.**P501:** Dispose of contents/containers in accordance with local regulation.**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

| Ingredient | Weight % (Approx.) | CAS N° | EINECS N° |
|-----------------------------|---------------------------|---------------|------------------|
| Kaolin | 60% - 90% | 1332-58-7 | 310-194-1 |
| Quartz - Crystalline Silica | 10% - 30% | 14808-60-7 | 238-878-4 |
| Titanium Dioxide | 1% - 5% | 13463-67-7 | 136-675-5 |
| Water | 1% - 20% | 7732-18-5 | 215-185-5 |

SECTION 4: FIRST AID MEASURES**Inhalation**

If adverse effects occur, get immediate medical attention. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin

Wash immediately with soap and water. Get medical attention if irritation develops or persists.

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion

DO NOT induce vomiting. If swallowed, drink plenty of water, DO NOT induce vomiting. Never make an unconscious person vomit or drink fluids. Get medical attention.

Symptoms: Immediate

Eye irritation, skin irritation, respiratory tract irritation

Symptoms: Delayed

Gastrointestinal effects

SECTION 5: FIREFIGHTING MEASURES**Flammable Properties**

Product is non-flammable.

Use extinguishing agents appropriate for surrounding fire.

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Unsuitable Extinguishing Media

None known

Protective Equipment and Precautions for Firefighters

Use protective equipment appropriate for surrounding materials.

Fire Fighting Measures

No hazard expected

NFPA 704M Hazard Classification**Health: 2****Flammable: 0****Reactivity: 0****SECTION 6: ACCIDENTAL RELEASE MEASURES****Personal Precautions**

Keep unnecessary people away, isolate hazard area and deny entry. Wet material is slippery under foot.

Wear personal protective clothing and equipment, see Section 8.

Environmental Precautions

Avoid release to the environment.

Cleanup Methods

Collect spilled material in appropriate container for reuse or disposal.

SECTION 7: HANDLING AND STORAGE**Precautions for Safe Handling**

Avoid dust generation and accumulation. Do not use in poorly ventilated or confined spaces. Do not taste or swallow. Avoid inhalation or contact. Wash thoroughly after handling.

Conditions for Safe Storage

Store in a cool, dry place. Store in a well-ventilated area.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines:**

Follow standard occupational hygiene control methods and procedures. Use an approved respirator if exposure limits are exceeded or if irritation develops or persists.

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Component Exposure Limits:

| Hazardous Ingredient Weight % (Approx.) | CAS N° | OSHA PEL | ACGIH TLV | NIOSH REL |
|--|------------|--|--|--|
| Kaolin 60 – 90 % | 1332-58-7 | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) | 2 mg/m ³ (respirable dust) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| Quartz - Crystalline Silica 10 – 30 % | 14808-60-7 | 0.05 mg/m ³ (respirable dust) | 0.025 mg/m ³ (respirable dust) | 0.05 mg/m ³ (respirable dust) |
| Titanium Dioxide (Naturally Occurring) 1 – 5 % | 13463-67-7 | 15 mg/m ³ (total dust) | 10 mg/m ³ (total dust) | |

* Unless otherwise noted, all PEL and TLV are reported as 8 hour time weighted average (TWA).

Component Analysis

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation: Use exhaust ventilation, if required, to maintain dust concentration below recommended exposure limits.

Personal Protective Equipment

Respiratory Protection: Where there is potential for airborne exposure, use of a MSHA/NIOSH or OSHA/NIOSH approved respirator is recommended.

Eyes/Face: Wear side shield safety glasses or chemical resistant safety goggles.

Glove Recommendation: Rubber gloves are recommended for prolonged exposure.

Protective Clothing: Wear appropriate chemical resistant clothing. Contaminated clothing should be removed and laundered before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: solid

Color: white to gray

Odor: earthy odor

pH: 4-6 (aqueous solution)

Boiling Point: not applicable

Decomposition: loses crystalline water at > 500°C (930°F)

LEL: Not applicable

Vapor Pressure: not applicable

Density: Not applicable

Appearance: white to gray solid

Physical Form: powder to lump

Odor Threshold: not applicable

Melting Point: > 1500°C

Flash Point: will not ignite

Evaporation Rate: not applicable

UEL: not applicable

Vapor Density (air = 1): not applicable

Specific Gravity (water = 1): ~2.6 gm/cc

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Water Solubility: none**Auto Ignition:** will not ignite**Flow Point:** not applicable**VOC:** none**Coeff> Water/Oil Dist:** not applicable**Viscosity:** not applicable**Sublimation Point:** not applicable**SECTION 10: STABILITY AND REACTIVITY****Reactivity**

No reactive hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions

Will not oxidize or polymerize.

Conditions to avoid

None known.

Materials to Avoid (Incompatibilities)

None known.

Decomposition Products

When exposed to high temperatures, free quartz can change crystal structure to form tridymite (above 870 °C or cristobalite (above 1470 °C) which have greater health hazards than quartz. (Tridymite and cristobalite (TWA-TLV) = 0.025 mg/m³)

SECTION 11: TOXICOLOGICAL INFORMATION**Primary Route of Exposure** – Skin, Eye Contact, Inhalation, and Ingestion**Acute Health Hazards**

Eye contact may cause mechanical irritation.

Skin contact may aggravate existing dermatitis.

Inhalation from prolonged and continuous exposure to excessive quantities of dust may aggravate existing asthmatic or respiratory conditions.

Acute and Chronic Toxicity

May cause eye irritation, skin irritation, respiratory tract irritation, and gastrointestinal tract irritation.

May cause damage to respiratory tract through prolonged or repeated exposure.

Occupationally inhaled ball clay produced pulmonary fibrosis with sites of action being the lung, the lymph nodes and the hilus. Ball clay when taken orally over a long period of time can cause granulomas of the stomach.

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Exposure to quartz (the most stable and common form of crystalline silica) is responsible for the majority of clinically diagnosed silicosis. Silicosis is a fibronodular lung disease that occurs after occupational exposure to crystalline silica for 5 years or longer. Inhalation of quartz dusts may cause shortness of breath, limitation of chest expansion, dry cough, and a lessened capacity for work. Individuals with a pre-existing disease in, or a history of ailments involving the skin or respiratory tract, are at greater risk for developing adverse health effects when exposed to this material.

In humans, chronic intermittent exposure to quartz caused pulmonary fibrosis, cough, and difficulty breathing. Overexposure to crystalline silica may cause silicosis, a form of disabling, progressive, and sometimes fatal pulmonary fibrosis characterized by the presence of typical nodulation in the lungs. Tuberculosis frequently complicates silicosis and the risk for tuberculosis is also increased in workers exposed to silica who have no radiographic evidence of silicosis. Crystalline silica can cause silicotic lesions in such organs as the liver, spleen and bone marrow. In humans, a causal relationship exists between exposure to crystalline silica and the development of autoimmune diseases. In multi-dose studies with animals, long term inhalation of quartz affected the lungs, endocrine system, immune system and blood.

This product contains quartz (respirable) as an impurity. Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France.)

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Quartz - Crystalline Silica (14808-60-7) Oral LD50 Rat 500 mg/kg

Titanium dioxide (13463-67-7) Oral LD50 >10000 mg/kg

Water (7732-18-5) Oral LD50 Rat >90 mL/kg

Irritation/Corrosivity Data

May cause eye irritation, skin irritation, respiratory tract irritation, and gastrointestinal tract irritation.

Respiratory Sensitizer

No test data available

Dermal Sensitizer

No test data available

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Carcinogenicity**Component Carcinogenicity****Kaolin - CAS N° 1332-58-7****ACGIH:** A4 - Not Classifiable as a Human Carcinogen**Quartz - Crystalline Silica - CAS N° 14808-60-7****ACGIH:** A2 - Suspected Human Carcinogen**IARC:** Group 1 - Carcinogenic to humans**Titanium dioxide - CAS N° 13463-67-7****ACGIH:** A4 - Not Classifiable as a Human Carcinogen**IARC:** Group 2B - Possibly carcinogenic to humans**Mutagenic Data**

No information available

Reproductive Effects Data

No information available

Specific Organ Toxicity - Single Exposure

Target organs include ears, skin, respiratory system, and gastrointestinal tract.

Specific Organ Toxicity - Repeated Exposure

Causes damage to eyes, skin, respiratory system, and gastrointestinal tract through prolonged or repeated exposure.

Aspiration Hazard

No data available

Medical Conditions Aggravated by Exposure

Individuals with pre-existing eye disorders, skin disorders, respiratory disorders and/or gastrointestinal disorders may have increased susceptibility to the effects of exposure.

SECTION 12: ECOLOGICAL INFORMATION**Ecotoxicity**

No information available for the product.

Component Analysis - Aquatic Toxicity

No LOEL ecotoxicity data are available for this product's components. No information available for the product.

Bioaccumulation

No information available for the product.

Bioconcentration

This material is not believed to bioconcentrate.

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

Biodegradation

This product is made from a naturally occurring, abundant, innocuous mineral.

Persistence

This product is made from a naturally occurring, abundant, innocuous mineral.

Mobility in Soil

This product is insoluble in water.

Results of PBT and vPvB Assessment

Not relevant

Other Toxicity

May affect turbidity if discharged in large quantities to lakes, streams or sewers.

SECTION 13: DISPOSAL CONSIDERATIONS**Non-hazardous waste - RCRA (40 CFR 261)**

Dispose of waste materials in accordance with all local, state, and Federal requirements. This product may not be disposed of in waterways or sewers.

SECTION 14: TRANSPORT INFORMATION

EPA Waste Number: Not regulated

DOT Classification: Not regulated

IMO Classification: Not regulated

Internal UN: Not regulated

IMDG Code: This product is not considered to be a marine pollutant.

SECTION 15: REGULATORY INFORMATION

SARA Title III Section 302 Extremely Hazardous Substances: This product does not contain extremely hazardous substances subject to the reporting requirements of Section 302 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 355.

SARA Title III Section 311 and 312 Health and Physical Hazard Categories per 40 CFR 370.2:

| Immediate | Delayed | Fire | Pressure | Reactivity |
|-----------|---------|------|----------|------------|
| Yes | Yes | No | No | No |

SARA Section 313 Notification: This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

TSCA: Product is listed in Initial Inventory, Vol. 1, Appendix A, CAS No. 999999-99-4**CERCLA:** Ball clay is not a CERCLA listed hazardous substance.**California Proposition 65:**

WARNING: This product can expose you to chemicals, including crystalline silica, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

NJ Special Health Hazardous Substances List [4]: RTK Hazardous Substance List; Substance number 4016.**PA Special Hazardous Substances List:** Regulated under PA Code Chapter 323.**Stockholm Convention:** This product is not subject to the Stockholm Convention.**Montreal Protocol:** This product is not subject to the Montreal Protocol.**Rotterdam Convention:** This product is not subject to the Rotterdam Convention.**National Inventories:****DSL (Canada):** Listed**NDSL (Canada):** Not Listed**PICCS (Philippines):** Listed**KECL (Korea):** Listed**ENCS (MITI) (Japan):** Listed**AICS (Australia):** Listed**IECSC (China):** Listed**EINECS (Europe):** Listed**REACH Status:** Exempt (Annex v.7). Product is a naturally occurring mineral.

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

SECTION 16: OTHER INFORMATION

ACA HMIS Health rating 2
ACA HMIS Physical hazard rating 0
ACA HMIS Personal protection rating E
ACA HMIS Flammability rating 0

**Training**

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

Key / Legend

| | |
|-----------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists |
| AICS | Australian Inventory of Chemical Substances |
| CAS | Chemical Abstract Service |
| CERCLA | Comprehensive Environmental Response, Compensation and Liability Act |
| CFR | Code of Federal Regulations |
| CHEMTREC | Chemical Transportation Emergency Center |
| DOT | Department of Transportation |
| DSL | Canadian Domestic Substances List |
| EINECS | European Inventory of New and Existing Chemical Substances |
| ENCS | Existing and New Substances Inventory |
| EPA | Environmental Protection Agency |
| FDA | Food and Drug Administration |
| HMIS | Hazardous Materials Identification System |
| IARC | International Agency for Research on Cancer |
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| IMDG | International Maritime Dangerous Goods Code |
| IMO | International Maritime Organization |
| KECI | Korean Existing Chemicals Inventory |
| LEL | Lower Explosive Limit |
| LOLI | List of Lists |
| MITI | Japanese Ministry of international Trade and Industry |
| MSHA | Mine Safety and Health Administration |
| NDSL | Canadian Non-Domestic Substance List |

SAFETY DATA SHEET**SDS ID: GLS_GHS_001**

Product Name(s):

KTS Classic, Martin (#5, #5/L-1), OM#4, Super Strength 2, OM4-SB, FT-3, Super Seal #2, Tennessee (#1 R SGP, #1 SGP, #5, #6, #9, #10), Todd Light, TN Stone, Amguard Sp, Milby, New K-blend, Bell Dark, Jackson, J-2, KT 5711-S, L-1, Bright Coatings II, Kentucky (#5 Bond, #6 Bond, Stone, #15 Dark, Sp), #2161, KT #1-4, KT 5711, Super Seal, Engobe Select, Bell Gray, TLM5, XX Sagger, M-79, HTP, DC-1A, MB, Karblite, Morkast, SF Enamel, KT #1-4S, Bell Bottom, T Clay, Dresden M, Oak #2, KTS-2, CDL2, ER-8, Dale Ann, MC Ball, Todd Dark, JHF

| | |
|--------------|--|
| NIOSH | National Institute of Occupational Safety and Health |
| NFPA | National Fire Protection Agency |
| OSHA | Occupational Health and Safety Administration |
| PBT | Persistent Bioaccumulative Toxic Chemical |
| PEL | Permissible Exposure Limit |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances |
| RCRA | Resource Conservation and Recovery Act |
| REACH | Registration, Evaluation, Authorization and Restriction of Chemicals |
| RTK | Right to Know |
| SARA | Superfund Amendments and Reauthorization Act |
| SDS | Safety Data Sheet |
| STOT | Specific Target Organ Toxicity |
| TLV | Threshold Limit Value |
| TSCA | Toxic Substances Control Act |
| TWA | Time Weighted Average |
| UEL | Upper Explosive Limit |
| UN | United Nations |
| VOC | Volatile Organic Content |
| vPvB | Very Powerful Very Bioaccumulative |

Disclaimer

Such information is to the best of IMERYS knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. IMERYS NORTH AMERICA CERAMICS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

IMERYS is a business name that includes Imerys North America Ceramics of which Kentucky-Tennessee Clay Company is a member. Registered in the USA. Registered office: 100 Mansell Court East, Suite 300, Roswell, GA 30076.

Prepared By: Imerys North America Ceramics Technical Group.

END OF SHEET

SDS ID: GLS_GHS_001