# The Cleaning Resource

# SAFETY DATA SHEET

## 1. Identification

**Product identifier GR-1000 GRAFFITI REMOVER** 

Other means of identification

SDS number 576N-64A HIL00465 **Product code** 

Recommended use Graffiti Remover **Recommended restrictions** For Labeled Use Only Manufacturer/Importer/Supplier/Distributor information

Manufacturer

HILLYARD INDUSTRIES Company name **Address** 302 North Fourth St. St. Joseph, MO 64501

**Contact person** Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

regulatoryaffairs@hillyard.com E-mail

(800) 424-9300 **Emergency telephone #** 

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident

involving chemicals)

# 2. Hazard(s) identification

Physical hazards Flammable liquids Category 4 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 **Environmental hazards** Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

**OSHA** defined hazards Not classified.

Label elements



Signal word

Combustible liquid. Causes skin irritation. May cause an allergic skin reaction. Causes serious **Hazard statement** 

eye irritation. Toxic to aquatic life with long lasting effects.

**Precautionary statement** 

Prevention Keep away from flames and hot surfaces - No smoking. Avoid breathing mist/vapors. Wash

thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

Category 2

If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Response Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash

occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish. Collect spillage.

Material name: GR-1000 GRAFFITI REMOVER

SDS US HIL00465 Version #: 03 Revision date: 07-29-2021 Issue date: 06-05-2015

Store in a well-ventilated place. Keep cool. Storage

Buyer assumes all risk and liability associated with disposal of this product (original concentration Disposal

or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry

container for recycling or reconditioning.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butoxydiglycol	BUTOXYDIGLYCOL	112-34-5	30 - < 40
d-Limonene		5989-27-5	10 - < 20
C9-11 Alcohols Ethoxylated	d	68439-46-3	3 - < 5
Other components below re		50 - < 60	

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special

treatment needed **General information**  Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air

mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

# 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

HIL00465 Version #: 03 Revision date: 07-29-2021 Issue date: 06-05-2015

# Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

# Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US.	<b>ACGIH</b>	Threshold	Limit Values	3
-----	--------------	-----------	--------------	---

Components	Туре	Value	Form
Butoxydiglycol (CAS	TWA	10 ppm	Inhalable fraction and
112-34-5)			vapor.

# Biological limit values

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to

maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency

shower must be available when handling this product.

No biological exposure limits noted for the ingredient(s).

## Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Use safety eyewear with splash guards or side shields, chemical goggles,

or face shields.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Avoid contact with the skin. If contact is likely, wear protective clothing appropriate to use

conditions.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards None known

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

Appearance Clear, colorless liquid

Physical state Liquid.
Form Liquid.
Color Colorless

Material name: GR-1000 GRAFFITI REMOVER
HIL00465 Version #: 03 Revision date: 07-29-2021 Issue date: 06-05-2015

Odor Non-objectionable Mild solvent odor

**Odor threshold** Not available. Ηq Not available.

Melting point/freezing point Not applicable / Not available Initial boiling point and boiling

range

> 340 °F (> 171.11 °C)

Flash point 150.0 °F (65.6 °C) Tag Closed Cup

**Evaporation rate** < 1 Ethyl ether=1 Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available. Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Vapor pressure 0.35 mm Hg

5.39 Vapor density

0.997 at 77°F Relative density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature Viscosity** Not available.

Other information

Density 8.30 lbs/gal **Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing. Percent volatile 95 - 97 %

VOC 13 % CARB VOC

96 % US EPA

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

**Acute toxicity** Not known.

Material name: GR-1000 GRAFFITI REMOVER

HIL00465 Version #: 03 Revision date: 07-29-2021 Issue date: 06-05-2015

Product Species Test Results

**GR-1000 GRAFFITI REMOVER** 

<u>Acute</u>

**Dermal** 

LD50 Rabbit 8182 mg/kg

Inhalation

LC50 Rat 450000 mg/l, 1 Hours

Oral

LD50 Rat 13630 mg/kg
Components Species Test Results

Butoxydiglycol (CAS 112-34-5)

Acute Dermal

LD50 Rabbit 2700 mg/kg

Oral

LD50 Rat 4500 mg/kg

d-Limonene (CAS 5989-27-5)

<u>Acute</u>

Oral

LD50 Mouse 5600 - 6600 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

d-Limonene (CAS 5989-27-5)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Product Species Test Results

GR-1000 GRAFFITI REMOVER

Aquatic

Crustacea EC50 Daphnia 109.4554 mg/l, 48 hours estimated

Fish LC50 Fish 4.6354 mg/l, 96 hours estimated

Material name: GR-1000 GRAFFITI REMOVER

Components Species Test Results

Butoxydiglycol (CAS 112-34-5)

**Aquatic** 

Fish LC50 Bluegill (Lepomis macrochirus) 1300 mg/l, 96 hours

C9-11 Alcohols Ethoxylated (CAS 68439-46-3)

**Aquatic** 

Crustacea EC50 Water flea (Daphnia magna) 2.9 - 8.5 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 6 - 12 mg/l, 96 hours

d-Limonene (CAS 5989-27-5)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 69.6 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butoxydiglycol 0.56 d-Limonene 4.57

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not established.

**General information** IMDG Regulated Marine Pollutant. This material is regulated under IATA and IMDG regulations.

Contact manufacturer for shipping instructions.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory

or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Flammable (gases, aerosols, liquids, or solids)

categories Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

## SARA 313 (TRI reporting)

Classified hazard

Not regulated.

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations**California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

#### International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)\*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 06-05-2015

 Revision date
 07-29-2021

Version # 03

HMIS® ratings Health: 2

Flammability: 2 Physical hazard: 0

**Disclaimer**No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

**Revision information**This document has undergone significant changes and should be reviewed in its entirety.

HIL00465 Version #: 03 Revision date: 07-29-2021 Issue date: 06-05-2015